




External Hex	2 Series	1.22 Hex (M2)  TSH2 TSHZ2 BSH2*	QUAD (M2)  GSQ2 GSQZ2	SLOTTED (M2)  TSS2 TSSZ2 GSS2 GSSZ2 BSS2*	UNIGRIP (M2)  TSU2 TSUZ2 GSU2 GSUZ2	TORQUE: 32-40Ncm Head Diameter: 2.70mm
	3 Series	 TSH3 TSHZ3 BSH3*	 GSQ3 GSQZ3	 TSS3 TSSZ3 GSS3 GSSZ3 BSS3*	 TSU3 TSUZ3 GSU3 GSUZ3	TORQUE: 32-40Ncm Head Diameter: 2.40mm
	INPi	1.22 Hex (M1.6)  TSH16 BSH16*	TORQUE: 32Ncm Head Diameter: 2.40mm	Piccolo 1.22 Hex (M1.6)  TS-P-16 BS-P-16*	TORQUE: 25-32Ncm Head Diameter: 2.15mm	Note: Screw TORQUE with PEEK Prosthetics: 15Ncm Note: Due to design revisions and changes, screw tips may be flat or rounded.

DC (Deep Conical)	1.22 Hex						1.22 Hex Passive Abutment Screws										
	M1.4		M1.6		M2		M1.4		M1.6		M2						
																	
	TS-DC3-14 BS-DC3-14*		TS-DC4-16 BS-DC4-16*		TS-DC5-20 TS-DC5-20*		PA-DC3-14T PA-DC3-14B* (anodized yellow)		PA-DC4-16T PA-DC4-16B* (anodized blue)		PA-DC5-20T PA-DC5-20B* (anodized purple)						
	Note: Screw TORQUE with PEEK Prosthetics: DC3 interface 15Ncm Screw TORQUE with PEEK Prosthetics: DC4 interface 20Ncm Screw TORQUE with PEEK Prosthetics: DC5 interface 20Ncm						DC3 TORQUE: 15Ncm Head Diameter: 2.10mm DC4 TORQUE: 20Ncm Head Diameter: 2.35mm DC5 TORQUE: 25-32Ncm Head Diameter: 2.35mm						PA-DC3-14T PA-DC3-14B* (anodized yellow) Head Diameter: 2.20mm TORQUE: 15Ncm PA-DC4-16T PA-DC4-16B* (anodized blue) Head Diameter: 2.40mm TORQUE: 20Ncm PA-DC5-20T PA-DC5-20B* (anodized purple) Head Diameter: 2.80mm TORQUE: 25 - 32Ncm				

Internal Hex (M-series & PROVATA)	1.27 Hex (M1.8)		Quad (M1.8)	TORQUE: 32Ncm Head Diameter: 2.25mm	1.27 Hex Passive Abutment Screws (M1.8)			TORQUE: 32Ncm Head Diameter: 2.60mm
								
	TS-Z-18	BS-Z-18*	GS-Q-18		PA-M-18T	PA-Q-18G	PA-M-18B*	
	Note: Screw TORQUE with PEEK Prosthetics: 15Ncm							

IT (Internal Octagon)	Torx (M2)	 TSIT2 GSIT2 BSIT2*	Torx Passive Abutment Screws (M2)	 TS-IT-PA BS-IT-PA*	TORQUE: 32-40Ncm Head Diameter: 2.70mm

NOTE:

Always ensure that the correct screw is used for the relevant implant and component.

***Blackened Brass Screws for Laboratory Use Only - Torque values do not apply.**

TRI-NEX	Unigrip (M1.8)				TORQUE: 32Ncm Head Diameter: 2.50mm	Unigrip (M2)				TORQUE: 32-40Ncm Head Diameter: 2.50mm													
																							
	TS-L-18	TS-L-18C (coated)	GS-L-18	BS-L-18*		TS-L-20	TS-L-20C (coated)	GS-L-20	BS-L-20*														
Note: Screw TORQUE with PEEK Prosthetics: 15Ncm											Note: Screw TORQUE with PEEK Prosthetics: 20Ncm												
Unigrip Passive Abutment Screws (M1.8)						TORQUE: 32Ncm Head Diameter: 2.70mm	Unigrip Passive Abutment Screws (M2)						TORQUE: 32-40Ncm Head Diameter: 2.70mm										
  							  																
PA-L-18							PA-L-20																
PA-L-18G							PA-L-20G																
PA-L-18B*							PA-L-20B*																
Compact Conical Abutment Level Screws	Series 1 Screws (M1.4)										TORQUE: 10-15Ncm Head Diameter: 2.25mm												
	1.22 Hex			Slotted			Unigrip																
																							
TSH1												TSS1											
GSH1												GSS1											
BSH1*												BSS1*											
TSU1												GSU1											
GSU1																							
Note: Screw TORQUE with PEEK Prosthetics: 10 - 15Ncm																							
Angled Compact Conical Abutment Screws	Series 9 & 9Z Screws (M2)										TORQUE: 20Ncm Head Diameter: 2.50mm	Internal Hex (M-series & PROVATA)	1.27 Hex		TORQUE: 32Ncm Head Diameter: 2.20mm								
	Slotted		Unigrip																				
																							
GSS9												TSU9											
TSU9												GSU9											
GSU9												TSUZ9											
TSUZ9												GSUZ9											
GSUZ9																							
DC (Deep Conical)	1.22 Hex						Unigrip				TORQUE: 15Ncm Head Diameter: 2.0mm	TRI-NEX	Unigrip				TORQUE: 20Ncm Head Diameter: 2.0mm			TORQUE: 20Ncm Head Diameter: 2.45mm			
																							
	TS-DC3-MC		TS-DC4-MC		TU-MCL-18C (coated)		GU-MCL-18		TU-MCL-20C (coated)		GU-MCL-20												
Special Screw (M2)	Unigrip										TORQUE: 20Ncm	Procera System	Unigrip (M2)				TORQUE: 32-40Ncm Head Diameter: 2.50mm						
													 										
GU-CL-9												TSP2		TSP2C (coated)									
Screw Connections	Hexed		Unigrip		Quad		Slotted		Torx				G.. = Gold Alloy		T.. = Gr. 5 Titanium Alloy		B.. = Brass						
			